

# FENTAN GTS

Rev. Date 12.2017

## DESCRIPTION

Heterocyclic poly condensed compound

## PHYSICAL CONSTANTS

		<i>Standard Value</i>	
Appearance	:	Colourless to yellowish liquid	
Active substance (%)	:	24%	$\pm 2$
pH (1:10)	:	9	$\pm 1$

## PROPERTIES

FENTAN GTS is recommended on wet blue where firmness is strongly compromised or in articles where a fine grain and gumminess are required even after milling.

## USE

FENTAN GTS is added during the rechroming operations at pH around 4.2-4.5. Addition beforehand of Sodium Formiate, to achieve this p>H, it will helps its penetration. FENTAN GTS allows better and excellent exhaustion of the chromium baths.

Used in pre-tanning on pickled FENTAN GTS allows the preparation of wet white and a considerable saving of tanning and retanning agents in the classic tanning processes. In combination with both vegetable and synthetic tanning agents, FENTAN GTS provides a softer, fuller and markedly lighter leather when compared to leather produced without the use of this tanning agent.

## PACKAGING

120 kg drums or 1000 kg mini-tanks.

## STORAGE

Store in a cool, dry, well-ventilated area between +5 and 40°C. Keep from freezing. For safe use of the product, the information given on the safety data sheet should be carefully observed.

## MINIMUM SHELF-LIFE

The product is guaranteed for its physical and quality characteristics for at least 24 months from the date of production. It must be kept well-sealed and stored in its original packaging according to the conditions on the technical and safety data sheets.

# FENTAN GTS/W

Rev. Date 12.2017

## DESCRIPTION

FENTAN GTS/W aldehyde tanning agent.

## PHYSICAL CONSTANTS

		<i>Standard Value</i>	
Appearance	:	Colourless free-flowing liquid	
Active substance (%)	:	44%	± 2
pH (1:10)	:	5	± 1

## PROPERTIES

FENTAN GTS/W is an aldehyde tanning agent that can become fixed within a wide pH range.

It can be used as pre-tanning agent with a shrinkage temperature around 58-60°C. Better if it is used at pH 6-7.

Field of applications:

- in the pretannage of woolled sheepskins, it boosts their degreasing.
- in the pretannage of chrome tanned skins and hides it improves the exhaustion of the chrome liquor.
- in the tannage it gives a better fixation.

## USE

FENTAN GTS/W is particularly suited for "eco" leathers and it represents an excellent re-tanning agent for improving the fullness, the feel, and the resistances.

FENTAN GTS/W is very fast to light.

## PACKAGING

125 kg drums or 1000 kg mini-tanks.

## STORAGE

Store in a cool, dry, well-ventilated area between +5 and 40°C. Keep from freezing.

For safe use of the product, the information given on the safety data sheet should be carefully observed.

## MINIMUM SHELF-LIFE

The product is guaranteed for its physical and quality characteristics for at least 24 months from the date of production. It must be kept well-sealed and stored in its original packaging according to the conditions on the technical and safety data sheets.